

7. Isolation logic for use in transferring information over a transformer between first and second control devices, the isolation logic comprising

a modulator that generates a pulse width modulated (PWM) signal encoding an analog frequency shift keying (FSK) signal to be transferred between the first and second control devices, and

the modulator being coupled to the transformer and applying the PWM signal thereto.

8. Isolation logic according to claim 7, wherein

the modulator is associated with a first one of the control devices,

the modulator applies the PWM signal to the transformer to effect transfer of the FSK signal encoded therein from the first control device to the second control device.

9. Isolation logic according to claim 8, wherein the modulator is coupled to a modem that generates the FSK signal to be transferred

10. Isolation logic according to claim 9, wherein

the modem is coupled to the first control device and receives therefrom a digital signal containing information to be transferred from the first control device to the second control device,

the modem generates the FSK signal from the digital signal.

11. Isolation logic according to any of claims 7 - 10, wherein each of the first and second control devices include any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control.
12. Isolation logic according to any of claims 7 - 10, wherein the FSK signal is compatible with any of a FoxComm™, HART™ or other analog control signal format.
13. Isolation logic according to any of claims 7 - 10 adapted for galvanic isolation across an isolation barrier.
14. An input/output module for use in any of industrial, manufacturing, service, environmental, or process control to transfer information over an isolation barrier between first and second control devices, the isolation logic comprising

transformer logic that inductively transfers a pulse width modulated (PWM) signal across the isolation barrier, the PWM signal having encoded therein an analog frequency shift keying (FSK) signal being transferred from the first to the second control device, and

the transformer logic inductively transferring an amplitude modulated (AM) signal across the isolation barrier, the AM signal having encoded therein an analog FSK signal being transferred from the second to the first control device.
15. An input/output module according to claim 14, wherein the transformer logic includes a first transformer that inductively transfers the PWM signals and second transformer that inductively transfers the AM signals.

16. An input/output module according to claim 14, comprising a first modulator that is coupled to the transformer logic, the first modulator generating and applying to the transformer logic the PWM signal during a period in which an FSK signal is to be transferred from the first control device to the second control device.
17. An input/output module according to claim 16, wherein the first modulator generates and applies to the transformer logic a signal of fixed duty cycle during a period in which an FSK signal is not being transferred from the first control device to the second control device.
18. An input/output module according to claim 17, comprising a second modulator that is coupled with the transformer logic, the second modulator generating the AM signal utilizing the signal of fixed duty cycle as a carrier signal.
19. An input/output module according to claim 18, wherein

the second modulator is coupled to the second control device and receives therefrom an FSK signal encoding information to be transferred from the second control device to the first control device, and

the second modulator generates the AM signal by modulating the carrier signal in accord with the FSK signal received from the second control device.
20. An input/output module according to claim 19, wherein the second modulator generates the AM signal by multiplying the carrier signal by the FSK signal received from the second control device.
21. An input/output module according to any of claims 14 - 20, wherein the FSK signal is compatible with any of a FoxComm™, HART™ or other analog control signal format.

- a first control device and a second control device, each of the first and second control devices including any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control,

a first modulator that is coupled to the first analog source, the first modulator generating a pulse width modulated (PWM) signal having encoded therein the first FSK signal,

a second analog source that generates a second analog FSK signal encoding information for transfer from the second control device to the first control device,

a second modulator that is coupled to the second analog source, the second modulator generating an amplitude modulated (AM) signal having encoded therein the second FSK signal,

56

1. The first step in the process of identifying a problem is to recognize that a problem exists. This is often done by comparing current performance with a desired state or goal. If there is a significant difference, a problem is identified.

28. A control system according to claim 23, wherein the first analog source is a modem.
29. A control system according to claim 28, wherein the modem coupled to the first control device and receives therefrom a digital signal encoding the information to be transferred to the second control device.
30. A control system according to any of claims 21 - 29, wherein the FSK signals are compatible with any of a FoxComm™, HART™ or other analog control signal format.
31. A control system according to any of claims 21 - 29, wherein each of the first and second control devices include any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control.
32. In a method of operating a process control system of the type having a transformer that transfers an analog frequency shift keying (FSK) signal across an isolation barrier, the improvement comprising encoding the FSK signal to be transferred by the transformer in a pulse width modulated (PWM) signal.
33. A method of transferring an analog frequency shift keying (FSK) signal over a transformer between first and second control devices, the method comprising the steps of

generating a pulse width modulated (PWM) signal encoding the FSK signal to be transferred between the first and second control devices, and

applying the PWM signal to the transformer for transfer between the first and second control devices.

inductively transferring a pulse width modulated (PWM) signal across the isolation barrier, the PWM signal having encoded therein an analog frequency shift keying (FSK) signal containing information being transferred from the first to the second control device, and

inductively transferring an amplitude modulated (AM) signal across the isolation barrier, the AM signal having encoded therein a FSK signal containing information being transferred from the second to the first control device.

40. A method according to claim 39, comprising inductively transferring the PWM signals using a first transformer and inductively transferring the AM signals using a second transformer.
41. A method according to claim 39, comprising generating and inductively transferring the PWM signal during a period in which an FSK signal is to be transferred from the first control device to the second control device.
42. A method according to claim 41, comprising generating and inductively transferring a signal of fixed duty cycle during a period in which an FSK signal is not being transferred from the first control device to the second control device.
43. A method according to claim 42, comprising generating the AM signal utilizing the signal of fixed duty cycle as a carrier signal.
44. A method according to any of claims 39 - 43, wherein the FSK signals are compatible with any of a FoxComm™, HART™ or other analog control signal format.
45. A method according to any of claims 39 - 43, wherein each of the first and second control devices include any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control.
46. A method of operating A method of operating a control system comprising,

generating a first analog frequency shift keying (FSK) signal encoding information for transfer from a first control device to a second control device, each of the first and second control devices

including any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control,

generating a pulse width modulated (PWM) signal having encoded therein the first FSK signal,

generating a second FSK signal encoding information for transfer from the second control device to the first control device,

generating an amplitude modulated (AM) signal having encoded therein the second FSK signal,

inductively transferring the PWM and AM signals across an isolation barrier.

47. A method of operating a control system according to claim 46, comprising responding to the PWM signal transferred by the transformer to generate a further FSK signal encoding the information being transferred from the first control device to the second control device.
48. A method of operating a control system according to claim 47, comprising responding to the AM signal transferred by the transformer to generate a further FSK signal encoding the information being transferred from the second control device to the first control device.
49. A method of operating a control system according to any of claims 44 - 48, wherein the FSK signals are compatible with any of a FoxComm™, HART™ or other analog control signal format.
50. A method of operating a control system according to any of claims 44 - 48, wherein each of the first and second control devices include any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control.